



Wi-PATH™ SX7T CDMA-EVDO

Fixed Cellular Terminal • Voice / Fax / Data

Telular's SX7 for 3G networks instantly enables high-quality voice, wireless broadband, and fax services over a single wireless network.

The flexible and economical SX7 is ideal for a variety of applications including wireline replacement, portable dial tone and least-cost routing.

Office in a Box

The SX7 is a portable unit with multiple standard connections to support a variety of office equipment, devices and peripherals. This flexibility allows users to instantly set up an office anywhere there is cellular coverage, providing service to one person or a full staff.

Cost-Effective Remote, Mobile or Small Office Solution

The ability to access the wireless world while being mobile or in remote locations is key to increasing productivity, business continuity, scalability and safety. The SX7 bridges or extends the physical range of analog to digital communications without disrupting, replacing or investing heavily in new network infrastructure.

Quick and Easy to Install

The plug and play features of the SX7 provide users with dial tone service within minutes, thus eliminating installation costs and wait times. The terminal's simple desktop or wall-mount installation options allow users the flexibility required for temporary offices with limited space. Additionally, the SX7 is AC powered and has an internal rechargeable battery back up unit, which means that low battery or power outages are no longer an issue.

Powerful Antenna Performance

The SX7 series has an extremely powerful and sensitive antenna that out performs most mobile devices currently on the market. The antenna allows the unit to connect to networks in areas a typical mobile device cannot, extending connectivity to the farthest fringes of the network and into rural areas.



Users without Landline Access



Telular SX7



Cellular Network

THE SX7 MEETS THE NEEDS OF MANY USERS

Retail - Cut the Cord

- Portable and easy to install connectivity
- Economical alternative to mandatory, but often unused, wireline

Remote and Temporary Office

- Extends productivity to the network's edge
- Cost-effective reuse as sites change

Government

- Robust, mobile communications for mission-critical operations
- Supports circuit-switched data (CSD)
 - *network dependant*

Industrial Control

- Enables the remote monitoring of assets without a land line
- Improves system uptime through wireless notifications



SX7T CDMA-EVDO UNIT SPECIFICATIONS

Air Interface Standard	EVDO, 1X RTT, Dual Band (800/1900MHz)
Input Connectors	USB Type B RJ45 Dual RJ11 Barrel Type Power Connector TNC Antenna Connector
Antenna Type	2dBi High Performance Antenna
Transmit Power	800/1900: 250mW

POWER

Power Requirements	110 / 230 VAC (at 50-60Hz)
Power Plug Options	US, UK and European
Rechargeable Battery Backup	Talk Time: 3 Hours Standby Time: 5 Hours Recharge Time: 5 Hours

PHYSICAL

Dimensions	8.13" x 5.5" x 1.8" (20.65cm x 13.97cm x 4.57cm)
Weight	Unit (unit, antenna and power supply): 1.9 lbs (862g) Battery: 0.5 lbs (227g)

ENVIRONMENTAL

Temperature Range	0 to 50 °C
Humidity	5 to 95%, non-condensing

CERTIFICATIONS

Regulatory	FCC Part 15, 22 and 24, RoHS, CDMA - CTIA
------------	---



Telular Corporation
2727 Paces Ferry Road
Suite 1-800

Atlanta, GA 30339 USA
1-800-229-2326
www.Telular.com